


The tables shows available dimensions in mm for direct order. The dimensions are valid when Strenx[®] 600MC D/E are delivered as cut lengths with mill edges in black condition.

Strenx[®] 600MC D/E is available in length up to 16000 mm. Before placing an order with length over 13600 mm, please contact your local sales representative for more information regarding suitable transportation options.

 Some restrictions, contact your local sales representative for more information.

 Outside the range of dimensions.

Width (mm)	760-	1061-	1091-	1141-	1191-	1316-	1326-	1361-	1391-	1401-	1501-	1541-	1551-	1601-
Thickness (mm)	1060	1090	1140	1190	1315	1325	1360	1390	1400	1500	1540	1550	1600	1640
2.00 - 2.24														
2.25 - 2.49														
2.50 - 2.74														
2.75 - 2.99														
3.00 - 3.24														
3.25 - 3.74														
3.75 - 3.99														
4.00 - 4.49			Maximum length 16000 mm											
4.50 - 7.49														
7.50 - 8.00														
8.01 - 8.49														
8.50 - 10.00														
10.1 - 25.0														
25.1 - 26.0														
26.1 - 27.0														

Shown widths are valid for normal width tolerance -0/+20 mm.

Dimensional limitations

- Min. length 1500 mm.
- Min. bundle weight 2 ton.
- Min position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width.
- Delivery weight accuracy +/- 10 %, at least -2 tons / + 3 tons.