



# Strenx® 1100 E/F

2020-11-19

The table shows available dimensions for direct order including the maximum length (mm).

 Some restrictions, contact your local sales representative for more information.

 Outside the range of dimensions.

Minimum length: 2000 mm<sup>\*)</sup>

Minimum quantities:

Thickness:

Minimum position weight:

4.0 - 40.0

2.5 tons

Width (mm)	1000-	-1351	1501	-1601	-1700	-1801	-1901	-2001	-2101	-2201	-2301	-2401	-2501	-2601	-2701	-2801	-2901	-3001	-3101	-3201	-3301	
Thickness (mm)	1350	1500	1600	1699	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3350	
3.0 - 3.9																						
4.0 - 4.7																						
4.8 - 5.7																						
5.8 - 6.0																						
6.1 - 6.7																						
6.8 - 7.7																						
7.8 - 8.7																						
8.8 - 10.0																						
10.1 - 25.0																						
25.1 - 26.0																						
26.1 - 27.0																						
27.1 - 28.0																						
28.1 - 29.0																						
29.1 - 30.0																						
30.1 - 31.0																						
31.1 - 32.0																						
32.1 - 33.0	14200																					
33.1 - 34.0	13800																					
34.1 - 35.0	13400												14500									
35.1 - 36.0	13100												14100									
36.1 - 37.0	12700											14300	13700									
37.1 - 38.0	12400										14500	13900	13400									
38.1 - 39.0	12000										14200	13600	13000									
39.1 - 40.0	11700									14400	13800	13200	12700									
40.1 - 45.0																						
45.1 - 50.0																						
50.1 - 55.0																						
55.1 - 60.0																						
60.1 - 65.0																						
65.1 - 70.0																						
70.1 - 75.0																						
75.1 - 80.0																						

<sup>\*)</sup> Minimum length when ordering one single plate is 3700 mm. Minimum order quantity is 2 plates when order length is less than 3700 mm.