


The tables shows available dimensions in mm for direct order including the maximum length. The dimensions are valid when Strenx<sup>®</sup> 960MC D/E and 960 Plus are delivered as cut lengths with mill edges in black conditions. The dimensions for Strenx<sup>®</sup> 960 CR are valid when the delivery condition is cut length with normal tolerances.

 Some restrictions, contact your local sales representative for more information.

 Outside the range of dimensions.

## Strenx<sup>®</sup> 960MC

Width (mm)	870-	1001-	1351-	1401-	1481-	1501-	1526-	1551-	1601-	1626-	1651-	1676-	1701-	1726-	1751-	1801-
Thickness (mm)	1000	1350	1400	1480	1500	1525	1550	1600	1625	1650	1675	1700-	1725	1750	1800	1860
2.00 - 2.99																
3.00 - 3.09																
3.10 - 3.19																
3.20 - 3.49																
3.50 - 3.99																
4.00 - 4.49																
4.50 - 4.79																
4.80 - 4.99																
5.00 - 5.99																
6.00 - 6.50																
6.51 - 6.99																
7.00 - 8.00																
8.01 - 8.99																
9.00 - 10.0																
10.1 - 25.0																
25.1 - 26.0																
26.1 - 27.0																

### Dimensional limitations

- Min. length 1500 mm
- Min. bundle weight 2 ton
- Min position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width.
- Delivery weight accuracy +/- 10 %, at least -2 tons / + 3 tons.

Shown widths are valid for normal width tolerance -0 /+20 mm

## Strenx<sup>®</sup> 960 Plus

Width (mm)	880-	1141-	1201-	1251-	1301-	1471-	1511-	1531-	1551-	1601-
Thickness (mm)	1140	1200	1250	1300	1470	1510	1530	1550	1600	1800
2.00 - 2.24										
2.25 - 2.49										
2.50 - 2.74										
2.75 - 2.99										
3.00 - 3.24										
3.25 - 3.74										
3.75 - 3.99										
4.00 - 4.99										
5.00 - 5.99										
6.00 - 6.40										
6.41 - 6.50										
6.51 - 6.99										
7.00 - 8.00										
8.01 - 8.99										
9.00 - 10.0										
10.1 - 25.0										
25.1 - 26.0										
26.1 - 27.0										

Shown widths are valid for normal width tolerance -0 /+20 mm

\*Before placing an order with length over 13600 mm, please contact your local sales representative for more information regarding suitable transportation options.

## Strenx<sup>®</sup> 960 CR

Width (mm)	800-	1001-	1201-	1251-	1301-	1351-	1401-	1478-	1518-
Thickness (mm)	1000	1200	1250	1300	1350	1400	1477	1517	1527
0.70 - 0.79									
0.80 - 0.94									
0.95 - 0.99									
1.00 - 1.09									
1.10 - 1.29									
1.30 - 1.69									
1.70 - 2.00									
2.01 - 2.10									
2.11 - 3.00									

Preferred length is 1000 - 8000 mm.