



The tables shows available dimensions in mm for direct order including the maximum length. The dimensions are valid when Strenx® 1100MC are delivered as cut lengths with mill edges in black condition. The dimensions for Strenx® 1100 CR are valid when the delivery condition is cut length with normal tolerances.

 Some restrictions, contact your local sales representative for more information.

 Outside the range of dimensions.

Strenx® 1100MC

Width (mm)	870-	1001-	1351-	1401-	1481-	1501-	1526-	1551-	1601-	1626-	1676-	1701-	1751-	1776-
Thickness (mm)	1000	1350	1400	1480	1500	1525	1550	1600	1625	1675	1700	1750	1775	1800
2.00 - 2.99														
3.00 - 3.09														
3.10 - 3.19														
3.20 - 3.49														
3.50 - 3.99														
4.00 - 4.49														
4.50 - 4.79														
4.80 - 4.99														
5.00 - 5.99														
6.00 - 6.40														
6.41 - 6.50														
6.51 - 6.99														
7.00 - 8.00														
8.01 - 8.99														
9.00 - 10.00														
10.1 - 25.0														
25.1 - 26.0														
26.1 - 27.0														

Dimensional limitations

- Min. length 1500 mm
- Min. bundle weight 2 ton
- Min position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width.
- Delivery weight accuracy +/- 10 %, at least -2 tons / + 3 tons.

Shown widths are valid for normal width tolerance -0/+20 mm

*Before placing an order with length over 13600 mm, please contact your local sales representative for more information regarding suitable transportation options.

Strenx® 1100 CR

Width (mm)	800-	1001-	1201-	1251-	1301-	1351-	1398-	1451-	1526-
Thickness (mm)	1000	1200	1250	1300	1350	1397	1450	1527	1600
0.70 - 0.79									
0.80 - 0.94									
0.95 - 0.99									
1.00 - 1.09									
1.10 - 2.00									
2.01 - 2.10									
2.11 - 3.00									

Preferred length is 1000 - 8000 mm.