



Strenx[®] 700 CR/MC/MC Plus

2022-03-17

The tables shows available dimensions in mm for direct order including the maximum length. The dimensions are valid when Strenx[®] 700MC D/E and 700MC Plus are delivered as cut lengths with mill edges in black condition. The dimensions for Strenx[®] 700 CR are valid when the delivery condition is cut length with normal tolerances.

 Some restrictions, contact your local sales representative for more information.

 Outside the range of dimensions.

Strenx[®] 700MC D/E

Width (mm)	760-	1061-	1091-	1141-	1191-	1281-	1361-	1391-	1401-	1431-	1526-	1541-	1551-
Thickness (mm)	1060	1090	1140	1190	1280	1360	1390	1400	1430	1525	1540	1550	1600
2.00 - 2.24													
2.25 - 2.49													
2.50 - 2.74													
2.75 - 2.99													
3.00 - 3.24													
3.25 - 3.49													
3.50 - 3.99													
4.00 - 4.49													
4.50 - 4.99			Maximum length 16000* mm										
5.00 - 8.00													
8.01 - 8.15													
8.16 - 9.39													
9.40 - 9.49													
9.50 - 10.00													
10.01 - 25.0													
25.01 - 27.0													

Shown widths are valid for normal width tolerance -0/+20 mm.

*Before placing an order with length over 13600 mm, please contact your local sales representative for more information regarding suitable transportation options.

Strenx[®] 700MC Plus

Width (mm)	870-	1001-	1161-	1231-	1251-	1301-	1351-	1431-	1451-	1501-	1526-	
Thickness (mm)	1000	1160	1230	1250	1300	1350	1430	1450	1500	1525	1600	
2.00 - 2.99												
3.00 - 3.49												
3.50 - 3.99												
4.00 - 4.99												
5.00 - 5.99												
6.00 - 6.81												
6.82 - 7.99		Maximum length 12300 mm										
8.00 - 9.00												
9.01 - 9.99												
10.00 - 10.20												
10.21 - 11.99												
12.00 - 12.00												
12.00 - 12.00												
12.01 - 26.00												
26.10 - 27.00												

Shown widths are valid for normal width tolerance -0/+20 mm.

Strenx[®] 700 CR

Width (mm)	750-	1001-	1201-	1251-	1301-	1351-	1371-	1451-	1551-
Thickness (mm)	1000	1200	1250	1300	1350	1370	1450	1500	1600
0.50 - 0.69									
0.70 - 0.79									
0.80 - 0.94									
0.95 - 1.09									
1.10 - 1.49	Maximum length 8500 mm								
1.50 - 2.00									
2.01 - 2.10									
2.11 - 3.00									

Preferred length is 1000 - 8000 mm.

Dimensional limitations

- Min. length 1500 mm.
- Min. bundle weight 2 ton.
- Min position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width.
- Delivery weight accuracy +/- 10 %, at least -2 tons / + 3 tons.