Hardox® HiAce plate

2026-08-21

The table shows available dimensions in mm for direct order including the maximum length in mm.

Some restrictions, contact your local sales representative for information

Outside the range of dimensions

Minimum lenght: 2000 mm*)

Minimum quantities:

Thickness:	Min. position weight:
3.0 - 60.0	2.5 tons
60.1 - 100.0	3.5 tons

Width	1000-	1351-	1501-	1601-	1701-	1801-	1901-	2001-	2101-	2201-	2301-	2401-	2501-	2601-	2701-	2751-	2801-	2901-	3001-	3101-	3201-	3301-
Thickness (mm)	1350	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2750	2800	2900	3000	3100	3200	3300	3350
3.0 - 3.9																						
4.0 - 4.7																						
4.8 - 5.7																						
5.8 - 6.7																						
6.8 - 7.7																						
7.8 - 8.7																						
8.8 - 10.0																						
10.1 - 24.0																						
24.1 - 25.0																						
25.1 - 26.0																						
26.1 - 27.0																					14200	14000
27.1 - 28.0																				14200	13700	13500
28.1 - 29.0																			14100	13700	13300	13100
29.1 - 30.0					Maximum length 14630 mm													14100	13600	13200	12800	12600
30.1 - 31.0																	14100	13600	13200	12800	12400	12200
31.1 - 32.0															14200	14200	13700	13200	12800	12400	12000	11800
32.1 - 33.0	14200													14200	13700	13700	13300	12800	12400	12000	11600	11500
33.1 - 34.0	13800												14400	13800	13300	13300	12900	12400	12000	11700	11300	11100
34.1 - 35.0	13400											14500	13900	13400	12900	12900	12500	12100	11700	11300	11000	10800
35.1 - 36.0	13100											14100	13600	13100	12600	12600	12200	11700	11400	11000	10700	10500
36.1 - 37.0	12700										14300	13700	13200	12700	12200	12200	11800	11400	11100	10700	10400	10200
37.1 - 38.0	12400									14500	13900	13400	12800	12400	11900	11900	11500	11100	10800	10400	10100	10000
38.1 - 39.0	12000									14200	13600	13000	12500	12000	11600	11600	11200	10800	10500	10200	9800	9700
39.1 - 40.0	11700								14400	13800	13200	12700	12200	11700	11300	11300	10900	10600	10200	9900	9600	9500
40.1 - 45.0	10400						14100	13400	12800	12300	11700	11300	10800	10400	10100	10100	9700	9400	9100	8800	8500	8400
45.1 - 50.0	9400				14100	13400	12700	12100	11500	11000	10600	10100	9700	9400	9000	9000	8700	8400	8200	7900	7700	7600
50.1 - 55.0	9000		14400	13600	12800	12100	11500	11000	10500	10000	9600	9200	9000	9000	9000	9000	7900	7700	7400	7200	7000	6900
55.1 - 60.0	8600	14100	13200	12400	11700	11100	10600	10100	9600	9200	9000	9000	8900	8600	8300	8300	7300	7000	6800	6600	6400	6300
60.1 - 65.0	7900	13000	11200	11200	10800	10300	9700	9300	9000	9000	8900	8500	8200	7900	7600	7600	6700	6500	6300			
65.1 - 70.0	7300	12100	11200	10700	10100	9500	9000	9000	8900	8600	8200	7900	7600	7300	7000	7000	6200					
70.1 - 75.0	6800	11300	10600	10000	9400	9000	9000	8700	8300	7900	7600	7300	7000	6800	6500							
75.1 - 80.0	6300	10600	9900	9400	9000	8900	8500	8100	7700	7400	7100	6800	6600	6300	6100							
80.1 - 85.0		8800	8800	8800	8800	8400	8000	7600	7300	7000	6700	6400	6100	5900	5700							
85.1 - 90.0		8300	8300	8300	8300	7900	7500	7200	6800	6500	6300	6000	5800	5500	5300							
90.1 - 95.0		7900	7900	7900	7900	7500	7100	6800	6400	6200	6000	5700	5400	5200	5000							
95.1 - 100.0		7500	7500	7500	7400	7100	6700	6400	6100	5800	5600	5400	5100	4900	4800							
100.1 - 105.0																						

* Minimum length when ordering one single plate is 3700 mm. Minimum order quantity is 2 plates when order length is less than 3700 mm.

Hardox® HiAce sheet

The table shows available dimensions in mm for direct order including maximum length.
Cut lengths with mill edges, black.

Some restrictions on dimensions and quantities, contact your local sales representative for information

Outside the range of dimensions

Min. length 1500 mm

Min. bundle weight 2 ton

Width (mm)	880-	1001-	1201-	1251-	1301-	1471-	1511-	1531-	1571-	1626-	1626-
Thickness (mm)	1000	1200	1250	1300	1470	1510	1530	1570	1625	1650	1650
2.00 - 2.49											
2.50 - 2.99											
3.00 - 3.24											
3.25 - 3.74											
3.75 - 3.99		Maximum length 16000 mm									
4.00 - 4.00											
4.01 - 5.00											
5.01 - 6.00											
6.01 - 6.30											
6.41 - 6.50											
6.51 - 7.00											
7.10 - 8.00											
8.10 - 10.0											
10.1 - 25.0											
25.1 - 26.0											
26.1 - 27.0											

Min position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width.
Delivery weight accuracy +/- 10 %, at least -2 tons / + 3 tons.

SSAB