

# Strenx® 900 E/F

2021-01-20

The table shows available dimensions for direct order including the maximum length (mm).

Strenx® 900 E is available in thickness up to 120.0 mm and Strenx® 900 F is available in thickness up to 100.0 mm.

Some restrictions, contact your local sales representative for more information.

Only 1650 mm width, mill edges -0/+70 mm. Other dimensions must be approved by Product Manager Strenx®.  
For thermally cut edges, contact local sales force.

Outside the range of dimensions.

Minimum length: 2000 mm<sup>\*)</sup>

Minimum quantities:

Thickness: Minimum position weight:

3.0 - 60.0 2.5 tons

60.1 - 100.0 3.5 tons

100.1 - 120.0 4.0 tons

Width (mm)	1000-	1351-	1501-	1650	1601-	1701-	1801-	1901-	2001-	2101-	2201-	2301-	2401-	2501-	2601-	2701-	2801-	2901-	3001-	3101-	3201-	3301-	
Thickness (mm)	1350	1500	1600		1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3350	
3.0 - 3.9																							
4.0 - 4.7																							
4.8 - 5.7																							
5.8 - 6.0																							
6.1 - 6.7																							
6.8 - 7.7																							
7.8 - 8.7																							
8.8 - 10.0																							
10.1 - 25.0																							
25.1 - 26.0																							14600
26.1 - 27.0																						14200	14000
27.1 - 28.0																					14200	13700	13500
28.1 - 29.0																				14100	13700	13300	13100
29.1 - 30.0																				14100	13600	13200	12600
30.1 - 31.0																				14100	13600	12800	12200
31.1 - 32.0																				14200	13700	13200	11800
32.1 - 33.0	14200																			14200	13700	13300	11500
33.1 - 34.0	13800																			14200	13700	13300	11100
34.1 - 35.0	13400																			14200	13700	13300	10800
35.1 - 36.0	13100																			14200	13700	13300	10500
36.1 - 37.0	12700																			14200	13700	13300	10200
37.1 - 38.0	12400																			14200	13700	13300	10000
38.1 - 39.0	12000																			14200	13700	13300	9700
39.1 - 40.0	11700																			14200	13700	13300	9500
40.1 - 45.0	10400																			14200	13700	13300	8400
45.1 - 50.0	9400																			14200	13700	13300	7600
50.1 - 55.0	9000																			14200	13700	13300	
55.1 - 60.0	8600	14100	13200		12400	11700	11100	10600	10100	9600	9200	9000	9000	8900	8600	8300	7300	7000	6800				
60.1 - 65.0	7900	13000	11200		11200	10800	10300	9700	9300	9000	9000	8900	8500	8200	7900	7600							
65.1 - 70.0	7300	12100	11200	12100	10700	10100	9500	9000	9000	8900	8600	8200	7900	7600	7300	7000							
70.1 - 75.0	6800	11300	10600	11300	10000	9400	9000	9000	8700	8300	7900	7600	7300										
75.1 - 80.0	6300	10600	9900	10600	9400	9000	8900	8500	8100	7700	7400	7100	6800										
80.1 - 85.0	5900	9900	9300	10000	8800	8800	8400	8000															
85.1 - 90.0	5500	9400	9000	9400	7900	8300	7900	7500															
90.1 - 95.0	5200	9000	8800	8800	7500	7900	7400	7100															
95.1 - 100.0	4900	8900	8300	8500	7100	7400	7000	6700															
100.1 - 105.0	4700	8400	7900	8000	7100	7100	6700	6400															
105.1 - 110.0	4400	8000	7500	7700	6800	6700	6400	6100															
110.1 - 115.0	4200	7600	7200	7300	6500	6400	6100	5800															
115.1 - 120.0	4000	7300	6800	7000	6200	6100	5800	5500															
120.1 - 125.0																							
125.1 - 130.0																							
130.1 - 135.0																							
135.1 - 140.0																							

<sup>\*)</sup> Minimum length when ordering one single plate is 3700 mm. Minimum order quantity is 2 plates when order length is less than 3700 mm.