

The table shows available dimensions for direct order including the maximum length (mm).
Strenx® 700 E is available in thickness up to 160 mm and Strenx® 700 F is available in thickness up to 130 mm.

Some restrictions, contact your local sales representative for more information.

Outside the range of dimensions.

Minimum length: 2000 mm^{a)}
Minimum quantities:
Thickness: Minimum position weight:
3.0 - 60.0 2.5 tons
60.1 - 100.0 3.5 tons
100.1 - 120.0 4.0 tons
120.1 - 5.0 tons

Width (mm)	1000-	1351-	1501-	1601-	1700-	1801-	1901-	2001-	2101-	2201-	2301-	2401-	2501-	2601-	2701-	2751-	2801-	2901-	3001-	3101-	3201-	3301-
Thickness (mm)	1350	1500	1600	1699	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2750	2800	2900	3000	3100	3200	3300	3350
3.0 - 3.9																						
4.0 - 4.7																						
4.8 - 5.7																						
5.8 - 6.0																						
6.1 - 6.7																						
6.8 - 7.7																						
7.8 - 8.7																						
8.8 - 10.0																						
10.1 - 25.0																						
25.1 - 26.0																						14600
26.1 - 27.0																					14200	14000
27.1 - 28.0																				14200	13700	13500
28.1 - 29.0																				14100	13700	13100
29.1 - 30.0																			14100	13600	13200	12600
30.1 - 31.0																			14100	13600	13200	12200
31.1 - 32.0																			14100	13600	13200	11800
32.1 - 33.0	14200																		14100	13600	13200	11500
33.1 - 34.0	13800																		14100	13600	13200	11100
34.1 - 35.0	13400																		14100	13600	13200	10800
35.1 - 36.0	13100																		14100	13600	13200	10500
36.1 - 37.0	12700																		14100	13600	13200	10200
37.1 - 38.0	12400																		14100	13600	13200	10000
38.1 - 39.0	12000																		14100	13600	13200	9700
39.1 - 40.0	11700																		14100	13600	13200	9500
40.1 - 45.0	10400																		14100	13600	13200	8400
45.1 - 50.0	9400																		14100	13600	13200	7600
50.1 - 55.0	9000																		14100	13600	13200	6900
55.1 - 60.0	8600	14100	13200	12400	11700	11100	10600	10100	9600	9200	9000	8900	8600	8300	8300	8300	7300	7000	6800	6600	6400	6300
60.1 - 65.0	7900	13000	11200	11200	10800	10300	9700	9300	9000	8900	8500	8200	7900	7600	7600	7600	6700	6500	6300			
65.1 - 70.0	7300	12100	11200	10700	10100	9500	9000	9000	8900	8600	8200	7900	7600	7300	7000	7000	6200					
70.1 - 75.0	6800	11300	10600	10000	9400	9000	9000	8700	8300	7900	7600	7300	7000	6800	6500							
75.1 - 80.0	6300	10600	9900	9400	9000	8900	8500	8100	7700	7400	7100	6800	6600	6300	6100							
80.1 - 85.0	5900	9900	9300	8800	8800	8400	8000	7600	7300	6900	6700	6400	6100	5900	5700							
85.1 - 90.0	5500	9400	9000	8300	8300	7900	7500	7200	6800	6500	6300	6000	5800	5500	5300							
90.1 - 95.0	5200	9000	8800	7900	7900	7400	7100	6700	6400	6200	5900	5700	5400	5200	5000							
95.1 - 100.0	4900	8900	8300	7500	7400	7000	6700	6400	6100	5800	5600	5300	5100	4900	4800							
100.1 - 105.0	4700	8400	7900	7100	7100	6700	6400	6100	5800	5500	5300	5100	4900	4700	4500							
105.1 - 110.0	4400	8000	7500	6800	6700	6400	6000	5800	5500	5200	5000	4800	4600	4400	4300							
110.1 - 115.0	4200	7600	7200	6500	6400	6100	5800	5500	5200	5000	4800	4600	4400	4200	4100							
115.1 - 120.0	4000	7300	6800	6200	6100	5800	5500	5200	5000	4800	4600	4400	4200	4000	3900							
120.1 - 125.0	3800	7000	6600	5900	5800	5500	5200	5000	4800	4500	4400	4200	4000	3800	3700							
125.1 - 130.0	3700	6700	6300	5700	5600	5300	5000	4800	4600	4400	4200	4000	3800	3700								
130.1 - 135.0		6400	6000	5500	5400	5100	4800	4600	4400	4200	4000	3800										
135.1 - 140.0		6200	5800	5300	5200	4900	4600															
140.1 - 145.0				5100																		
145.1 - 150.0				4900																		
150.1 - 155.0				4800																		
155.1 - 160.0				4600																		

^{a)} Minimum length when ordering one single plate is 3700 mm. Minimum order quantity is 2 plates when order length is less than 3700 mm.