



The tables shows available dimensions in mm for direct order including the maximum length. The dimensions are valid when Strenx[®] 700 HR W and 960 HR W are delivered as cut lengths with mill edges in black condition.

 Some restrictions, contact your local sales representative for more information.

 Outside the range of dimensions.

Strenx[®] 700 HR W

Width (mm)	870-	1141-	1201-	1281-	1286-	1431-	1526-	1541-	1551-	1601-
Thickness (mm)	1140	1200	1280	1285	1430	1525	1540	1550	1600	1800
2.00 - 2.24										
2.25 - 2.49										
2.50 - 2.74										
2.75 - 2.99										
3.00 - 3.49										
3.50 - 3.99										
4.00 - 4.59										
4.60 - 4.74		Maximum length 13600 mm								
4.75 - 4.99										
5.00 - 6.10										
6.11 - 6.99										
7.00 - 8.00										
8.01 - 8.99										
9.00 - 10.0										
10.1 - 25.0										
25.1 - 26.0										
26.1 - 27.0										

Shown widths are valid for normal width tolerance -0/+20 mm

Strenx[®] 960 HR W

Width (mm)	870-	1141-	1481-	1501-	1526-	1551-	1651-	1676-	1701-	1726-	1751-	1801-	1861-
Thickness (mm)	1140	1480	1500	1525	1550	1650	1675	1700	1725	1750	1800	1860	1900
2.00 - 2.49													
2.50 - 2.99													
3.00 - 3.09													
3.10 - 3.19													
3.20 - 3.49													
3.50 - 3.99													
4.00 - 4.49													
4.50 - 4.79													
4.80 - 4.99			Maximum length 12300 mm										
5.00 - 5.99													
6.00 - 6.10													
6.11 - 6.99													
7.00 - 8.99													
9.00 - 10.0													
10.1 - 25.0													
25.1 - 26.0													
26.1 - 27.0													

Shown widths are valid for normal width tolerance -0/+20 mm

Dimensional limitations

- Min. length 1500 mm
- Min. bundle weight 2 ton
- Min position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width.
- Delivery weight accuracy +/- 10 %, at least -2 tons / + 3 tons.